GENERAL®

Precision Measuring Instruments
with Excel-Formatted Data Logging SD Card

12 Channels
TEMPERATURE RECORDER

DT4208SD

Precision, Specialty and Innovation

Contents

Accurately Measures Air (Wind) Speed and Temperature

25.0
27.6 °C
m/S

POWER ESC
FUNC. HOLD NEXT
REC ENTER
Unit
☀
SET ▼
Time check
LOGGER ▲
Sampling check

SD Card Data Logger
ANEMOMETER
Type K/J Thermometer

GENERAL® DAF4207SD

ANEMOMETER VANE PROBE

No. DAF4207SD

Applications:
• Commercial/industrial ventilation
• Energy audits
• HVAC/R
• Paint spray booths

Industrial Vent

Energy Auditing

This instrument's unique feature is its patented technique for storing sampled data in Excel format on removable SD memory cards

2GB
SD
SD/2GB

Typical Excel Data

AM

Typical Excel Plotted Data

3

Anemometer-Thermometer
with Excel-Formatted Data Logging SD Card

Included Accessories:

- Hard carrying case
- Combination air-speed temperature probe
- 2GB SD memory card
- User's manual

Optional Accessories:

- 9VDC adapter for 110V power supply (General P/N AC1)
- Type K thermocouples
  General P/N TPK500 (-50° to 500°F)
  General P/N TPK05 (-40° to 562°F)
  General P/N TPK03 (-40° to 950°F)

No. DAF4207SD

Specifications:

Embedded Microcontroller: Custom one-chip LSI device

Display Type: LCD with green backlight

Display Size: 2.05 x 1.5 in. (52 x 38mm)

Parameters Measured: Air speed, temperature

Measurement Range:
- For air speed: 0.4 to 30m/sec, 1.4 to 126 km/hr, 0.9 to 78.3 mph, 0.8 to 68 knots, 79 to 6890 ft/min
- For temperature: 32° to 122°F (0° to 50°C)

Measurement Accuracy:
- For air speed: ± (2% + 0.2 m/sec), ± (2% + 0.8 km/hr), ± (2% + 0.4 mph), ± (2% + 0.4 knots), ± (2% + 40 ft/min)
- For temperature: ± 1.5oF (± 0.8°C)

Measurement Resolution:
- For air speed: 0.1 m/sec, 0.1 km/hr, 0.1 mph, 0.1 knots, 1.0 ft/min
- For temperature: 0.1°F or C

Data Logging Sampling Time: 1 second to 1 hour

Settable Parameters: Date, time, auto power off, beep sound, sampling time, decimal point or comma decimal division, temperature unit, air speed unit, optional thermocouple type (K or J)

Storable/Recallable Readings: Maximum, minimum

SD Card Capacity: 1GB to 16GB

Operating Temperature: 32° to 122°F (0° to 50°C)

Operating Relative Humidity: 0 to 85%

Power Supply: Six Alkaline "AA" batteries or optional 9-VDC AC adapter

Power Consumption
- 15 mADC (normal operation, with backlight off and SD card not saving data)
- 36 mADC with backlight on and card saving data
- 48mADC with backlight on and card saving data

Dimensions of Instrument:
7.99 x 2.99 x 1.50 in. (203 x 76 x 38mm)

Weight of Instrument: 1.13 lb. (515g)

Diameter of Probe Head: 2.83 in. (72mm)

Hot Wire Anemometer-Thermometer
with Excel-Formatted Data Logging SD Card

Accurately Measures Air (Wind) Speeds As Low As 0.5 mph and Air Temperatures within ±1.5°F (± 0.8°C)

No. HWA4214SD

Applications:

- Environmental testing
- Maintenance and repair of air conveyors and flow hoods in clean rooms
- Calibrating low-speed fans and blowers
- Balancing velocity profiles in furnaces and refrigerated cases
- Precision calibration of HVAC/R systems

Minimally Invasive Duct Leak Testing

Calibrating HVAC Systems

This instrument's unique feature is its patented technique for storing sampled data in Excel format on removable SD memory cards

Typical Excel Data

Typical Excel Plotted Data

Hot Wire Anemometer-Thermometer
with Excel-Formatted Data Logging SD Card

Included Accessories:

- Hard carrying case
- Telescoping air speed/ tempeature probe
- 2 GB SD memory card
- User's manual

Optional Accessories:

- 9VDC adapter for 110V power supply (General P/N AC1)
- Type K thermocouples
    General P/N TPK500 (-50° to 500°F)
    General P/N TPK05 (-40° to 562°F)
    General P/N TPK03 (-40° to 950°F)

No. HWA4214SD

Specifications:

Embedded Microcontroller: Custom one-chip LSI device

Display Type: LCD with green backlight

Display Size: 2.05 x 1.5 in. (52 x 38mm)

Parameters Measured: Air speed, temperature

Measurement Range:
- For air speed: 0.2 to 25 m/sec, 0.7 to 172 km/hr, 0.5 to 44.7 mph, 0.4 to 38.8 knots, 40 to 3940 ft/min
- For temperature: 32° to 122°F (0° to 50°C)

Measurement Accuracy:
- For air speed: ± (5% + 0.1 m/sec), ± (5% + 0.3 km/hr), ± (5% + 0.2 mph), ± (5% + 0.2 knots), ± (5% + 20 ft/min)
- For temperature: ± 1.5°F (± 0.8°C)

Measurement Resolution:
- For air speed: 0.01 m/sec (0.2 to 5.0 m/sec), 0.1 m/sec (5.1 to 25.0 m/sec); 0.01 km/hr (0.7 to 18 km/hr), 0.1 km/hr (18 to 72 km/hr); 0.01 mph (0.5 to 11.20 mph), 0.1 mph (11.2 to 44.7 mph); 0.01 knot (0.4 to 9.7 knots), 0.1 knot (9.7 to 38.8 knots); 1 ft/min (40 to 3940 ft/min)
- For temperature: 0.1° F or C

Data Logging Sampling Time: 1 second to 1 hour

Settable Parameters: Date, time, auto power off, beep sound, sampling time, decimal point or comma decimal division, temperature unit, air speed unit, optional thermocouple type (K or J)

Storable/Recallable Readings: Maximum, minimum

SD Card Capacity: 1 GB to 16 GB

Operating Temperature: 32° to 122°F (0° to 50°C)

Operating Relative Humidity: 0 to 85%

Power Supply: Six Alkaline "AA" batteries or optional 9-VDC AC adapter

Power Consumption:
- 30 mADC (normal operation, with backlight off and SD card not saving data)
- 50 mADC (with backlight on and card saving data)

Dimensions of Instrument: 7.99 x 2.99 x 1.50 in. (203 x 76 x 38mm)

Weight of Instrument: 1.13 lb. (515g)

Dimensions of Probe: 0.4724 in. (diameter) x 11.02 in.(collapsed)/37 in.(extended) (12mm x 280mm/940mm)

Accurately Measures Air (Wind) Speed + Temperature, Air Temperature + Humidity, Light & Sound Levels, Surface Temperature

Applications:
- Facilities management
- Environment control
- OSHA compliance

Facilities Management

Environment Control

No. DLAF930SD

This instrument's unique feature is its patented technique for storing sampled data in Excel format on removable SD memory cards

Typical Excel Data

Typical Excel Plotted Data

Included Accessories:

- Hard carrying case
- Combination temperature/ humidity/air speed/light level probe
- 2 GB SD memory card
- User's manual

Optional Accessories:

- 9VDC adapter for 110V power supply (General P/N AC1)
- Type K thermocouples
    General P/N TPK500 (-50° to 500°F)
    General P/N TPK05 (-40° to 562°F)
    General P/N TPK03 (-40° to 950°F)
- Sound level probe/plug adapter (General P/N SC941)

No. DLAF930SD

Specifications:

Embedded Microcontroller: Custom one-chip LSI device

Display Type: LCD with green backlight

Display Size: 2.05 x 1.5 in. (52 x 38mm)

Parameters Measured: Air temperature, relative humidity (R.H.), air speed, light level

Measurement Range:
- For air speed: 0.4 to 25 m/sec, 1.4 to 90 km/hr, 0.9 to 55.9 mph, 0.8 to 48.6 knots, 80 to 4930 ft/min
- For temperature: 32° to 122°F (0 to 50°C); for R.H., 10 to 95%
- For light level: 0 to 20,000 lux, 0 to 1860 ft-cd

Measurement Accuracy:
- For air speed: ± (2% + 0.2 m/sec), ± (2% + 0.8 km/hr), ± (2% + 0.4 mph), ± (2% + 0.4 knots), ± (2% + 40 ft/min)
- For temperature: 1.5°F (± 0.8°C)
- For humidity: ± (3% of reading + 1%) for R.H. values ≥70%; ± 3% of reading for R.H values < 70%
- For light level: ± (5% of reading ± 8 digits)

Measurement Resolution:
- For air speed: 0.1 m/sec, 0.1 km/hr, 0.1 mph, 0.1 knots, 1.0 ft/min
- For temperature: 0.1 °F or °C
- For humidity: 0.1% of reading
- For light level: 1 lux, 0.1 ft-cd

Data Logging Sampling Time: 1 second to 1 hour

Settable Parameters: Date, time, auto power off, beep sound, sampling time, decimal point or comma decimal division, temperature unit, air speed unit, light level unit, optional thermocouple type (K or J)

Storable/Recallable Readings: Maximum, minimum

SD Card Capacity: 1 GB to 16 GB

Operating Temperature: 32° to 122°F (0° to 50°C)

Operating Relative Humidity: 0 to 85%

Power Supply: Six Alkaline "AA" batteries or optional 9-VDC AC adapter

Power Consumption:
- 3.5 mADC (normal operation, with backlight off and SD card not saving data)
- 28 mADC with backlight on and card saving data
- 40mADC with backlight on and card saving data

Dimensions of Meter: 5.31 x 2.36 x 1.30 in. (135 x 60 x 33mm)

Weight of Meter: 1.13 lb. (515g)

Dimensions of Probe: 4.13 x 1.81 x 1.14 in. (105 x 46 x 29mm)

Accurately Measures Sound Levels of Machinery or an Environment with 0.1 dB Resolution

No. DSM402SD

Applications:

• Noise pollution control
• OSHA noise regulatory compliance
• Acoustics design

Noise Pollution Control

Acoustics Design

This instrument's unique feature is its patented technique for storing sampled data in Excel format on removable SD memory cards

Typical Excel Data

Typical Excel Plotted Data

Class 2 Sound Level Meter
with Excel-Formatted Data Logging SD Card

Included Accessories:

- Hard carrying case
- Sound wind shield ball
- 2 GB SD memory card
- User's manual

Optional Accessories:

- 9VDC adapter for 110V power supply (General P/N AC1)

No. DSM402SD

Specifications:

Embedded Microcontroller: Custom one-chip LSI device

Display Type: LCD with green backlight

Display Size: 2.05 x 1.5 in. (52 x 38 mm)

Parameter Measured: dB

Frequency Range: 31.5 Hz to 8 kHz

Measurement Range:
- 30 to 130 dB in autoranging mode
- User can also select fixed range of 30 to 80 dB, 50 to 100 dB, or 80 to 130 dB

Measurement Weighting:
- By frequency: frequency weighing uses "A" or "C" standard
- By time: time weighting is fast or slow (200 ms or 500 ms response time)

Measurement Accuracy:
- With "A" frequency weighting: ± 3.5 dB @ 31.5 Hz, 2. 5 dB @ 63 Hz, 2 dB @ 125 Hz, 1.9 dB @ 250 Hz, 1.9 dB @ 500 Hz, 1.4 dB @ 1 kHz, 2.6 dB @ 2 kHz, 3.6 dB @ 4 kHz, 5.6 dB @ 8 kHz

Measurement Resolution: 0.1 dB

Data Logging Sampling Time: 1 second to 1 hour

Settable Parameters: Date, time, auto power off, beep sound, sampling time, decimal point or comma decimal division, "A" or "C" frequency weighting, fast or slow time weighting

Storable/Recallable Readings: Maximum, minimum

SD Card Capacity: 1 GB to 16 GB

Operating Temperature: 32° to 122°F (0° to 50°C)

Operating Relative Humidity: 0 to 85%

Power Supply: Six Alkaline "AA" batteries or optional 9-VDC AC adapter

Power Consumption:
- 8 mADC (normal operation, with backlight off and SD card not saving data)
- 30 mADC with backlight on and card saving data
- 44 mADC with backlight on and card saving data

Dimensions of Meter:
9.65 x 2.68 x 1.77 in. (245 x 68 x 45mm)

Weight of Meter: 1.08 lb. (489g)

Accurately Measures Sound Levels of Machinery or an Environment with 0.1 dB Resolution

No. DSM403SD

Applications:

- Acoustics design
- Sound system setup
- OSHA compliance

Acoustics Design

Sound System Setup

This instrument's unique feature is its patented technique for storing sampled data in Excel format on removable SD memory cards

Typical Excel Data

Typical Excel Plotted Data

11

Class 1 Sound Level Meter
with Excel-Formatted Data Logging SD Card

Included Accessories:

- Hard carrying case
- Sound wind shield ball
- 2 GB SD memory card
- User's manual

Optional Accessories:

- 9VDC adapter for 110V power supply (General P/N AC1)

No. DSM403SD

Specifications:

Embedded Microcontroller: Custom one-chip LSI device

Display Type: LCD with green backlight

Display Size: 2.05 x 1.5 in. (52 x 38mm)

Parameter Measured: dB

Frequency Range: 31.5 Hz to 16 kHz

Measurement Range:
- 30 to 130 dB in autoranging mode
- User can also select fixed range of 30 to 80 dB, 50 to 100 dB, or 80 to 130 dB

Measurement Weighting:
- By frequency: using Class I IEC 61672 standard; frequency weighing uses "A" or "C" standard
- By time: using Class 1 IEC 61672 standard; time weighting is fast or slow (200 ms or 500 ms response time)

Measurement Accuracy:
- With "A" frequency weighting: ± 2.0 dB @ 31.5 Hz, 1.5 dB @ 63 Hz, 1.5 dB @ 125 Hz, 1.4 dB @ 250 Hz, 1.4 dB @ 500 Hz, 1.1 dB @ 1 kHz, 1.6 dB @ 2 kHz, 1.6 dB @ 4 kHz, +2.1 dB and -3.1dB @ 8 kHz; +3.0 dB and -6.0 dB @ 12.5 kHz, +3.5 dB and -17.0 dB @ 16 kHz

Measurement Resolution: 0.1 dB

Data Logging Sampling Time: 1 second to 1 hour

Settable Parameters: Date, time, auto power off, beep sound, sampling time, decimal point or comma decimal division, "A" or "C" frequency weighting, fast or slow time weighting

Storable/Recallable Readings: Maximum, minimum

SD Card Capacity: 1 GB to 16 GB

Operating Temperature: 32° to 122°F (0° to 50°C)

Operating Relative Humidity: 0 to 85%

Power Supply: Six Alkaline "AA" batteries or optional 9-VDC AC adapter

Power Consumption:
- 8 mADC (normal operation, with backlight off and SD card not saving data)
- 14 mADC with backlight on and card saving data
- 44 mADC with backlight on and card saving data

Dimensions of Meter:
9.65 x 2.68 x 1.77 in. (245 x 68 x 45mm)

Weight of Meter: 1.08 lb. (489g)

UVA, UVC Light Meter
with Excel-Formatted Data Logging SD Card

Accurately Measures UVA and UVC Light Intensity within Two Automatically Switched Full-Scale Ranges: 2 mW/cm^2 and 20 mW/cm^2

No. UV254SD

Applications:

- Welding
- UV food sterilization
- Photochemical matching
- Erasing memory chips
- Exposing photoresists
- Curing of inks, adhesives and coatings

Welding

UV Sterilization

This instrument's unique feature is its patented technique for storing sampled data in Excel format on removable SD memory cards

Typical Excel Data

Typical Excel Plotted Data

UVA, UVC Light Meter
with Excel-Formatted Data Logging SD Card

Included Accessories:

- UVA probe
- UVC probe
- 2 GB SD memory card
- Hard carrying case
- User's manual

Optional Accessories:

- 9VDC adapter for
  110V power supply
  (General P/N AC1)

No. UV254SD

Specifications:

Embedded Microcontroller: Custom one-chip LSI device

Display Type: LCD with green backlight

Display Size: 2.05 x 1.5 in. (52 x 38 mm)

UV Light Types Measured: UVA, UVC

Measurement Range: 240 nm to 390 nm

Measurement Accuracy: ±4% of full-scale reading
+ 2 digits

Full-Scale Autoranges: 2 mW/cm^2 and 20 mW/cm^2

Storable/Recallable Readings: Maximum, minimum

Data Logging Sampling Time: 1 second to 1 hour

SD Card Capacity: 1 GB to 16 GB

Settable Parameters: Date, time, auto power off, beep
sound, temperature unit (°F or °C),
sampling time, thermocouple type
(K or J), decimal point or comma

Operating Temperature: 32° to 122°F (0° to 50°C)

Operating Relative Humidity: 0 to 85%

Power Supply: Six Alkaline "AA" batteries
or optional 9-VDC AC adapter

Power Consumption:
- 6.5 mADC (normal operation, with backlight off
  and SD card not saving data)
- 30 mADC with backlight on

Dimensions of Meter:
6.97 x 2.68 x 1.77 in. (177 x 68 x 45mm)

Weight of meter: 12.38 oz. (351 g)

Dimensions of UVA Probe Head:
1.77 in. (diagonal) x 1.26 in. (L) (45 x 32 mm)

Dimensions of UVA Probe Handle:
0.94 in. (diagonal) x 4.92 in. (L) (24 x 125 mm)

Weight of UVA Probe: 3.53 oz. (100g)

Dimensions of UVC Probe:
1.50 (diagonal) x 0.98 in (L) (38 x 25 mm)

Weight of UVC Probe: 3.63 oz. (103g)

Light Meter
with Excel-Formatted Data Logging SD Card

Accurately Measures Light Intensity in Lux or Foot-Candles Using Three Automatically Switched Full-Scale Ranges

No. DLM112SD

Applications:

- OSHA compliance
- Industrial/commercial photography/videography
- Construction
- Engineering
- Surveillance/security

- The law requires the owner of a loading dock to provide a minimum of 1 foot candle illumination
- Defendant's loading dock fell far below OSHA's minimum lighting requirement
- Defendant violated OSHA's minimum illumination requirement and therefore Defendant's violation is negligent

An OSHA Citation

Industrial Photography

This instrument's unique feature is its patented technique for storing sampled data in Excel format on removable SD memory cards

Typical Excel Data

Typical Excel Plotted Data

Light Meter
with Excel-Formatted Data Logging SD Card

Included Accessories:

- Hard carrying case
- Light probe with protective cover
- 2 GB SD memory card
- User's manual

Optional Accessories:

- 9VDC adapter for 110V power supply (General P/N AC1)
- Type K thermocouples
  - General P/N TPK500 (-50° to 500°F)
  - General P/N TPK05 (-40° to 562°F)
  - General P/N TPK03 (-40° to 950°F)

No. DLM112SD

Specifications:

Embedded Microcontroller: Custom one-chip LSI device

Display Type: LCD with green backlight

Display Size: 2.05 x 1.5 in. (52 x 38mm)

Full-Scale Ranges:
- 0 to 1,999 lux (0 to 186 ft-cd)
- 1,800 to 19,990 lux (167 to 1,860 ft-cd)
- 18,000 to 99,900 lux (1,670 to 9,290.7 ft-cd)

Measurement Accuracy:
- ± 4% of full-scale reading + 2 digits for all lux readings and ft-cd readings at 200 ft-cd full-scale (f.s.)
- ± 4% of f.s. reading + 2 ft-cd at 2,000 ft-cd f.s.
- ±4% of f.s. reading + 20 ft-cd at 20,000 ft-cd f.s.

Measurement Resolution:
- 1 lux at 2,000 lux f.s.
- 10 lux at 20,000 lux f.s.
- 100 lux at 100,000 lux f.s.
- 0.1 ft-cd at 200 ft-cd f.s.
- 1 ft-cd at 2,000 ft-cd f.s.
- 10 ft-cd at 10,000 ft-cd f.s.

Storable/Recallable Readings: Maximum, minimum

Data Logging Sampling Time: 1 second to 1 hour

SD Card Capacity: 1 GB to 16 GB

Settable Parameters: Date, time, auto power off, beep sound, temperature unit (°F or °C), sampling time, thermocouple type (K or J), decimal point or comma

Operating Temperature: 32° to 122°F (0° to 50°C)

Operating Relative Humidity: 0 to 85%

Power Supply: Six Alkaline "AA" batteries or optional 9-VDC AC adapter

Power Consumption:
- 6.5 mADC (normal operation, with backlight off and SD card not saving data)
- 30 mADC with backlight on

Dimensions of Meter:
6.97 x 2.68 x 1.77 in. (177 x 68 x 45mm)

Weight of Meter: 1.08 lb. (489g)

Accurately Measures 4 Channels of Temperature from -148° to 3092°F (-100° to 1700°C)

No. DT4947SD

Applications:

- Food and chemical processing
- HVAC/R systems
- Power generation
- Paper production

Food Processing

Paper Production

This instrument's unique feature is its patented technique for storing sampled data in Excel format on removable SD memory cards

Typical Excel Data

Typical Excel Plotted Data

4-Channel Thermometer
with Excel-Formatted Data Logging SD Card

Included Accessories:

- Carrying case
- Two Type K beaded thermocouple probes
- 2 GB SD memory card
- User's manual

Optional Accessories:

- 9VDC adapter for 110V power supply (General P/N AC1)
- Pt 100 ohm RTD (General P/N RTDTP-100)
- Additional Type K thermocouples
  General P/N TPK500 (-50° to 500°F)
  General P/N TPK05 (-40° to 562°F)
  General P/N TPK03 (-40° to 950°F)

No. DT4947SD

Specifications:

Embedded Microcontroller: Custom one-chip LSI device

Display Type: LCD with green backlight

Display Size: 2.05 x 1.5 in. (52 x 38mm)

Parameter Measured: Temperature (in °F or °C)

Measurement Range:
- For Pt 100 ohm RTD: -327° to 1562°F
- For thermocouples: depends on type

Measurement Accuracy:
- For Pt 100 ohm probes: ± (4% of reading + 1.8°F) from -327° to 999.9°F, ± (4 % of reading + 2.0°F) from 1000° to 1562°F)
- For thermocouples: ± (4% of reading + 2.0°F max)

Measurement Resolution:
- For Pt 100 ohm probes: 0.1° (F or C) from -327° to 999.9°F, 1°F from 1000° to 1562°F
- For thermocouples: 0.1° (F or C) below 1000°F and 1° (F or C) above 1000°F for Types K, J, T and E; 1° (C or F) for Types R and S

Data Logging Sampling Time: 1 second to 1 hour

Settable Parameters: Date, time, decimal point or comma decimal division, auto power off, beep sound, temperature unit, sampling time

Storable/Recallable Readings: Maximum, minimum

SD Card Capacity: 1 GB to 16 GB

Operating Temperature: 32° to 122°F (0° to 50°C)

Operating Relative Humidity: 0 to 85%

Power Supply: Six Alkaline "AA" batteries or optional 9-VDC AC adapter

Power Consumption:
- 8.5 mADC (normal operation, with backlight off and SD card not saving data)
- 30 mADC with backlight on and card saving data
- 44 mADC with backlight on and card saving data

Dimensions of Thermometer:
6.97 x 2.68 x 1.77 in. (177 x 68 x 45mm)

Weight of Thermometer: 1.13 lb. (515g)

Accurately Measures 12 Channels of Temperature from -148° to 3092°F (-100° to 1700°C)

No. DT4208SD

Applications:

• Food and chemical processing

• PC board burn-in

• Paper production

• HVAC/R (heating, ventilation and air-conditioning/refrigeration)

• Power generation

Petrochemical Production

PC Board Burn-In

This instrument's unique feature is its patented technique for storing sampled data in Excel format on removable SD memory cards

Typical Excel Data

Typical Excel Plotted Data

Included Accessories:

- Hard carrying case
- Two Type K beaded thermocouple probes
- 2 GB SD memory card
- User's manual

Optional Accessories:

- 9VDC adapter for 110V power supply (General P/N AC1)
- Type K thermocouples
  General P/N TPK500 (-50° to 500°F)
  General P/N TPK05 (-40° to 562°F)
  General P/N TPK03 (-40° to 950°F)

No. DT4208SD

Specifications:

Embedded Microcontroller: Custom one-chip LSI device

Display Type: LCD with green backlight

Display Size: 2.05 x 1.5 in. (52 x 38mm)

Parameter Measured: Temperature (in °F or °C)

Measurement Range:
- Using supplied Type K thermocouples: -148° to 2372°F (-100° to 1300°C)
- For other thermocouples: depends on type

Measurement Accuracy:
- For supplied Type K thermocouples: ± (4 % of reading + 2.0°F max)

Measurement Resolution
- For supplied type K thermocouples: 0.1° (F or C) below 1000°F, 1° (F or C) above 1000°F

Data Logging Sampling Time: 1 second to 1 hour

Settable Parameters: Date, time, decimal point or comma decimal division, auto power off, beep sound, loop recording enable or disable, temperature unit, sampling time

Storable/Recallable Readings: Maximum, minimum

SD Card Capacity: 1 GB to 16 GB

Operating Temperature: 32° to 122°F (0° to 50°C)

Operating Relative Humidity: 0 to 85%

Power Supply: Six Alkaline "AA" batteries or optional 9-VDC AC adapter

Power Consumption:
- 7.5 mADC (normal operation, with backlight off and SD card not saving data)
- 25 mADC with backlight on and card saving data
- 36 mADC with backlight on and card saving data

Dimensions:
8.86 x 4.92x 2.52 in. (225 x 125 x 64mm)

Weight: 2.1 lb. (944g)

Pressure Meter
with Excel-Formatted Data Logging SD Card

Accurately Measures Hydraulic or Pneumatic Pressure Using Ten Different Units

Applications:

• Automotive
• Mechanical engineering/design
• HVAC/R systems
• Equipment MRO

Boiler Room Pump Maintenance

Hydraulic Valve Testing

No. PM930SD

This instrument's unique feature is its patented technique for storing sampled data in Excel format on removable SD memory cards

Typical Excel Data

Typical Excel Plotted Data

GENERAL®

No. PM930SD

Included Accessories:

- Carrying case
- 2 GB SD memory card
- User's manual

Optional Accessories:

- 9VDC adapter for 110V power supply (General P/N AC1)
- 2 bar full-scale pressure sensor (General P/N PS2)
- Pressure sensors:
    5 bar full-scale (General P/N PS5)
    10 bar full-scale (General P/N PS10)
    50 bar full-scale (General P/N PS50)
    100 bar full-scale (General P/N PS100)
    400 bar full-scale (General P/N PS400)

Specifications:

Embedded Microcontroller: Custom one-chip LSI device

Display Type: LCD with green backlight

Display Size: 2.05 x 1.5 in. (52 x 38mm)

Displayed Pressure Unit: bar, psi, inches Hg, inches H_2O, hPA, kPA, kg/cm^2, mm Hg, meters H_2O, atmospheres

Measurement Accuracy: ± 0.5% of full-scale reading + 1 digit

Storable/Recallable Readings: Maximum, minimum

Data Logging Sampling Time: 1 second to 9 hours

SD Card Capacity: 1 GB to 16 GB

Settable Parameters: Date, time, auto power off, beep sound, sampling time, decimal point or comma decimal division, optional pressure sensor's full-scale range (2, 5, 10, 20, 50, 100, 200 or 400 bar)

Operating Temperature: 32° to 122°F (0° to 50°C)

Operating Relative Humidity: 0 to 85%

Power Supply: Six Alkaline "AA" batteries or optional 9-VDC AC adapter

Power Consumption:
- 5 mADC (normal operation, with backlight off and SD card not saving data)
- 25 mADC with backlight on and card saving data
- 37 mADC with backlight on and card saving data

Dimensions of Meter:
6.97 x 2.68 x 1.77 in. (177 x 68 x 45mm)

Weight of Meter: 0.77 lb. (350g)

GENERAL®

General Tools & Instruments
80 White Street, New York, NY 10013-3567
TEL: 212. 431. 6100   TOLL FREE: 800. 697. 8665
sales@generaltools.com   www.generaltools.com

Humidity-Temperature Meter
with Excel-Formatted Data Logging SD Card

Accurately Measures Temperature and Relative Humidity of a Fluid Including Dew Point/Wet-Bulb Temperature of Ambient Air

Applications:
- HVAC/R systems
- Horticulture

Rooftop HVAC System

Horticulture

GENERAL® DTH3007SD

No. DTH3007SD

This instrument's unique feature is its patented technique for storing sampled data in Excel format on removable SD memory cards

Typical Excel Data

Typical Excel Plotted Data

GENERAL®

Included Accessories:

- Soft carrying case
- Temperature-humidity probe
- 2 GB SD memory card
- User's manual

Optional Accessories:

- Hard carrying case
- 9VDC adapter for 110V power supply (General P/N AC1)
- Type K thermocouples:
  - General P/N TPK500 (-50° to 500°F)
  - General P/N TPK05 (-40° to 562°F)
  - General P/N TPK03 (-40° to 950°F)

No. DTH3007SD

Specifications:

Embedded Microcontroller: Custom one-chip LSI device

Display Type: LCD with green backlight

Display Size: 2.05 x 1.5 in. (52 x 38mm)

Parameters Measured: Temperature, relative humidity (R.H.), dew point, wet-bulb temperature

Measurement Range:
- For temperature: 32° to 122°F (0° to 50°C)
- For R.H.: 5 to 95%;
- For dew point: -13.5° to 120.1°F (-25.3° to 48.9°C);
- For wet-bulb temperature: -6.9° to 122°F (-21.6° to 50°C)

Measurement Accuracy:
- ± 1.5°F (± 0.8°C) for temperature
- Sum of temperature and humidity accuracies for dew point and wet-bulb temperature

Measurement Resolution:
- 0.1° (F or C) for temperature and humidity

Data Logging Sampling Time: 1 second to 1 hour

Settable Parameters: Date, time, auto power off, beep sound, sampling time, decimal point or comma decimal division, temperature unit

Storable/Recallable Readings: Maximum, minimum

SD Card Capacity: 1 GB to 16 GB

Operating Temperature: 32° to 122°F (0° to 50°C)

Operating Relative Humidity: 0 to 85%

Power Supply: Six Alkaline "AA" batteries or optional 9-VDC AC adapter

Power Consumption::
- 3.5 mADC (normal operation, with backlight off and SD card not saving data)
- 28 mADC with backlight on and card saving data
- 40 mADC with backlight on and card saving data

Dimensions of Meter: 6.97 x 2.68 x 1.77 in. (177 x 68 x 45mm)

Weight of Meter: 1.08 lb. (489g)

GENERAL®

General Tools & Instruments
80 White Street, New York, NY 10013-3567
TEL: 212. 431. 6100   TOLL FREE: 800. 697. 8665
sales@generaltools.com   www.generaltools.com

Accurately Measures a Machine's Acceleration and Velocity to Determine if Its Within Operational Parameters

Applications:

• Performance testing/preventive maintenance of fans and motors

• Plant inspection

• Equipment production QC

Motor Performance Testing

Fan Balancing

No. VM8205SD

This instrument's unique feature is its patented technique for storing sampled data in Excel format on removable SD memory cards

Typical Excel Data

Typical Excel Plotted Data

Vibration Meter
with Excel-Formatted Data Logging SD Card

GENERAL®

Included Accessories:

- Hard carrying case
- Vibration sensing probe
- Magnetic base
- 2 GB SD memory card
- User's manual

Optional Accessories:

- 9VDC adapter for 110V power supply (General P/N AC1)

No. VM8205SD

Specifications:

Embedded Microcontroller: Custom one-chip LSI device

Display Type: LCD with green backlight

Display Size: 2.05 x 1.5 in. (52 x 38mm)

Parameters Measured: Acceleration, velocity

Units:
- For acceleration: m/sec^2, g (gravitational force) or ft/sec^2
- For velocity: mm/sec, cm/sec or inches/sec.

Displayed Value Options: Root mean square (RMS), peak, max hold

Input Frequency Range: 10 Hz to 1 kHz

Measurement Range:
- For acceleration: 0.5 to 199.9 m/sec^2, 0.05 to 20.39 g, 2 to 656 ft/sec^2
- For velocity: 0.5 to 199.9 mm/sec, 0.05 to 19.99 cm/sec, 0.02 to 7.87 inches/sec

Measurement Accuracy:
- For acceleration: ± (5% of reading + 2 digits)
- For velocity: ± (5% of reading + 2 digits)

Measurement Resolution:
- For acceleration: 0.1 m/sec^2, 0.01 g, 1 ft/sec^2
- For velocity: 0.1 m/sec, 0.01 inches/sec

Calibration Point:
- For acceleration: 50 m/sec^2 @ 160 Hz
- For velocity: 50 mm/sec @ 160 Hz

Data Logging Sampling Time: 1 second to 1 hour

Settable Parameters: Date, time, decimal point or comma decimal division, auto power off, beep sound, sampling time

Storable/Recallable Readings: Maximum, minimum, peak (RMS values only)

SD Card Capacity: 1 GB to 16 GB

Operating Temperature: 32° to 122°F (0° to 50°C)

Operating Relative Humidity: 0 to 85%

Power Supply: Six Alkaline "AA" batteries or optional 9-VDC AC adapter

Power Consumption:
- 15 mADC (normal operation, with backlight off and SD card not saving data)
- 36 mADC with backlight on and card saving data
- 48 mADC with backlight on and card saving data

Dimensions of Meter: 7.99 x 2.99 x 1.50 in. (203 x 76 x 38mm)

Weight of Meter: 1.13 lb. (515g)

Dimensions of Probe: 1.46 (length) x 0.63 (diameter) in. (37 x 16 mm)

Length of Probe Cable: 47.24 in. (1.2m)

Accurately Measures pH and ORP (Oxidation-Reduction Potential)

No. DPH230SD

Applications:

- Water conditioning
- Beverage production
- Wastewater monitoring
- Aquaculture (fish farming)
- Aquariums
- Pulp and paper processing
- Electroplating
- Photography

Water Conditioning

Beverage Production

This instrument's unique feature is its patented technique for storing sampled data in Excel format on removable SD memory cards

Typical Excel Data

Typical Excel Plotted Data

27

GENERAL®

Included Accessories:

- Carrying case
- 2 GB SD memory card
- User's manual

Optional Accessories:

- 9VDC adapter for 110V power supply (General P/N AC1)
- ORP probe (General P/N ORP14)
- Automatic temperature compensation (ATC) probe (General P/N TP07)
- Professional-grade 0 to 14 pH electrode (General P/N PHS1)

- Heavy-duty spear tip pH electrodes (General P/Ns PHS4HD and PHS6HD)
- Combination pH electrode/temperature probe (General P/N PHS5T)
- Combination pH electrode/temperature probe with automatic temperature compensation (General P/N PHS3K7)

No. DPH230SD

Specifications:

Embedded Microcontroller: Custom one-chip LSI device

Display Type: LCD with green backlight

Display Size: 2.05 x 1.5 in. (52 x 38mm)

Parameters Measured: pH, ORP

Measurement Range:
- For pH: 0 to 14
- For ORP: -1999 mV to +1999 mV

Measurement Accuracy:
- For pH: ± (0.02 pH units + 2 digits)
- For ORP: ± (0.5% of reading + 2 digits)

Measurement Resolution:
- For pH: 0.01 unit
- For ORP: 1 mV

Temperature Compensation:
- Automatic between 32° and 150°F (0° and 65°C) when using optional ATC temperature probe.
- Manually settable between 32° and 212°F (0° and 100°C) without ATC probe

Storable/Recallable Readings: Maximum, minimum

Data Logging Sampling Time: 1 second to 9 hours

SD Card Capacity: 1 GB to 16 GB

Settable Parameters: Date, time, auto power off, beep sound, sampling time, decimal point or comma decimal division, temperature unit, compensation temperature

Operating Temperature: 32° to 122°F (0° to 50°C)

Operating Relative Humidity: 0 to 85%

Power Supply: Six Alkaline "AA" batteries or optional 9-VDC AC adapter

Power Consumption:
- 14 mADC (normal operation, with backlight off and SD card not saving data)
- 37 mADC with backlight on and card saving data
- 49 mADC with backlight on and card saving data

Dimensions: 6.97 x 2.68 x 1.77 in. (177 x 68 x 45mm)

Weight: 1.08 lb. (489g)

Accurately Measures Any Solution's Conductivity, Total Dissolved Solids (TDS), Salt Content and Temperature

No. DCT430SD

Applications:
- Electroplating
- Water conditioning
- Wastewater monitoring
- Aquaculture (fish farming)

Wastewater Treatment

Salmon Farming

This instrument's unique feature is its patented technique for storing sampled data in Excel format on removable SD memory cards

	A	B	C	D
1	Position	Date	Time	Ch1_Value
2	1	2009/8/12	13:16:36	73.1
3	2	2009/8/12	13:16:38	73.2
4	3	2009/8/12	13:16:40	73.2
5	4	2009/8/12	13:16:42	73.2
6	5	2009/8/12	13:16:44	73.4
7	6	2009/8/12	13:16:46	73.5
8	7	2009/8/12	13:16:48	73.4
9	8	2009/8/12	13:16:50	73.4
10	9	2009/8/12	13:16:52	73.5
11	10	2009/8/12	13:16:54	73.3

Typical Excel Data

Typical Excel Plotted Data

Included Accessories:

- Hard carrying case
- Combination conductivity/TDS/salt probe (General P/N CDPB03)
- 2 GB SD memory card
- User's manual

Optional Accessories:

- 9VDC adapter for 110V power supply (General P/N AC1)

No. DCT430SD

Specifications:

Embedded Microcontroller: Custom one-chip LSI device

Display Type: LCD with green backlight

Display Size: 2.05 x 1.5 in. (52 x 38mm)

Probe Type: Carbon rod electrode

Parameters (units) Measured:
- Conductivity (uS, mS)
- Total dissolved solids (ppm)
- Salt content (% weight)
- Temperature (°F, °C)

Measurement Accuracy:
- For conductivity: +- 2% of full-scale reading +1 digit, TDS
- For temperature: ± 0.8°C/± 1.5°F
- For salt: ±0.5% of value

Measurement Resolution:
- For Conductivity: 0.1 uS @ 200 uS full-scale (f.s.), 0.001 mS @ 2 mS f.s., 0.01 mS @ 20 mS f.s., 0.1mS @ 200 mS f.s.
- For TDS: 0.1 ppm @200 ppm f.s., 1 ppm @ 2,000 ppm f.s., 10 ppm @ 20,000 ppm f.s., 100 ppm @ 100,000 ppm f.s.
- For Temperature: 0.1°F/0.1°C
- For Salt: 0.01%

Temperature Compensation:
- Automatic from 32° to 140°F (0° to 60°C)
- Temperature compensation factor is manually variable from 0 to 5% per degree Celsius

Storable/Recallable Readings: Maximum, minimum

Data Logging Sampling Time: 1 second to 9 hours

SD Card Capacity: 1 GB to 16 GB

Settable parameters: Date, time, auto power off, beep sound, sampling time, decimal point or comma decimal division, temperature unit, temperature compensation level

Operating Temperature:
- 32° to 122°F (0° to 50°C) for meter
- 32° to 140°F (0° to 60°C) for probe

Operating Relative Humidity: 0 to 85%

Power Supply: Six Alkaline "AA" batteries or optional 9-VDC AC adapter

Power Consumption:
- 14 mADC (normal operation, with backlight off and SD card not saving data)
- 37 mADC with backlight on and card saving data
- 49 mADC with backlight on and card saving data

Dimensions of Meter: 6.97 x 2.68 x 1.77 in. (177 x 68 x 45mm)

Weight of Meter: 1.08 lb. (489g)

Dimensions of Probe: 0.86 in. (diameter) x 4.72 in. (L) (22mm x 120mm)

Dissolved Oxygen Meter
with Excel-Formatted Data Logging SD Card

Accurately Measures Dissolved Oxygen Concentration of Liquid or Air

Applications:

- Aquaculture (fish farming)
- Water pollution control
- Food processing
- Photography
- Pulp and paper manufacturing
- Power generation
- Electroplating
- Facilities management

Water Pollution Control

Power Generation

No. DOM551SD

**This instrument's unique feature is its patented technique for storing sampled data in Excel format on removable SD memory cards**

	A	B	C	D	E
1	Position	Date	Time	Ch1_Value	Ch1_Unit
2	1	2009/8/12	13:38:29	7.8	mg/L
3	2	2009/8/12	13:38:30	7.8	mg/L
4	3	2009/8/12	13:38:32	7.8	mg/L
5	4	2009/8/12	13:38:34	7.6	mg/L
6	5	2009/8/12	13:38:36	7.6	mg/L
7	6	2009/8/12	13:38:38	7.6	mg/L
8	7	2009/8/12	13:38:40	7.5	mg/L
9	8	2009/8/12	13:38:42	7.5	mg/L
10	9	2009/8/12	13:38:44	7.5	mg/L
11	10	2009/8/12	13:38:46	7.5	mg/L

Typical Excel Data

Typical Excel Plotted Data

Dissolved Oxygen Meter
with Excel-Formatted Data Logging SD Card

Included Accessories:

- Hard carrying case
- Oxygen probe
- Probe-filling electrolyte
- Two spare probe heads and diaphragm set
- 2 GB SD memory card
- User's manual

Optional Accessories:

- 9VDC adapter for 110V power supply (General P/N AC1)

No. DOM551SD

Specifications:

Embedded Microcontroller: Custom single-chip LSI device

Display Type: LCD with green backlight

Display Size: 2.0 x 1.5 in. (52 x 38mm)

DO Measurement Range: 0 to 20 mg/L

DO Measurement Resolution: 0.1 mg/L

DO Measurement Accuracy: ± 0.4 mg/L

Oxygen in Air Measurement Range: 0 to 100%

Oxygen in Air Measurement Resolution: 0.1% O_2

Oxygen in Air Measurement Accuracy: ±0.7% O_2

Temperature Measurement Range: 32° to 122°F (0° to 50°C)

Temperature Measurement Resolution: 0.1 °F or °C

Temperature Measurement Accuracy: ±1.5 °F (±0.8 °C)

Compensation For Temperature: Automatic

Compensation For Altitude: 0 to 29,200 ft. (0 to 8,900m)

Compensation For Liquid Salt Content: 0 to 50%

Data Logging Sampling Time: 1 second to 9 hours

DO Probe Type: Polarographic

SD Memory Card Capacity: 1 GB to 16 GB

Power Supply: Six Alkaline "AA" batteries or 9-VDC adapter

Power Consumption:
- 14 mADC (normal operation, with backlight off and SD card not saving data)
- 37 mADC with backlight on and card not saving data
- 49 mADC with backlight on and card saving data

Operating Temperature: 32° to 122 °F (0° to 50°C)

Operating Relative Humidity: 0 to 85%

Dimensions of Meter: 7.0 x 2.7 x 1.9 in. (177 x 68 x 45mm)

Weight of Meter: 1.08 lb. (489g)

Dimensions of Probe: 7.5 (long) x 1.1 (across) inches (190 x 28mm)

Weight of Probe: 0.74 lb. (335g)

Accurately Measures Conductivity, Total Dissolved Solids (TDS) or Salt Concentration of a Liquid. Optional Probes Measure pH, ORP (Oxidation-Reduction Potential) and Dissolved Oxygen (DO)

No. WK2017SD

Applications:

- Water conditioning
- Wastewater monitoring and control
- Beverage production
- Aquaculture (fish farming)
- Pulp and paper processing
- Electroplating
- Photography

Beverage Production


Wastewater Monitoring

This instrument's unique feature is its patented technique for storing sampled data in Excel format on removable SD memory cards

Typical Excel Data

Typical Excel Plotted Data

Hour (a.m. or p.m.)

Included Accessories:

- Hard carrying case
- Combination conductivity/ TDS/salt probe (General P/N CDPB03)
- 2 GB SD memory card
- User's manual

Optional Accessories:

- 9VDC adapter for 110V power supply (General P/N AC1)
- ORP probe (General P/N ORP14)
- Automatic temperature compensation (ATC) probe (General P/N TP07)
- Oxygen probe (General P/N DOP2001)
- Professional-grade 0 to 14 pH electrode (General P/N PHS1)

- Heavy-duty spear tip pH electrodes (General P/Ns PHS4HD and PHS6HD)
- Combination pH electrode/temperature probe (General P/N PHS5T)
- Combination pH electrode/temperature probe with automatic temperature compensation (General P/N PHS3K7)

No. WK2017SD

Specifications:

Embedded Microcontroller: Custom one-chip LSI device

Display Type: LCD with green backlight

Display Size: 2.05 x 1.5 in. (52 x 38mm)

Parameters Measured: pH, ORP, conductivity, TDS content, DO content, salt content

Measurement Range:
- For pH: 0 to 14
- For ORP: -1999 mV to +1999 mV
- For conductivity: up to 200 mS (microSiemens)
- For TDS: up to 132,000 ppm
- For DO: up to 20 mg/L
- For salt: up to 12% by weight

Measurement Accuracy:
- For pH: ± (0.02 pH units + 2 digits)
- For ORP: ± (0.5% of reading + 2 digits)
- For conductivity: ± 2% of full-scale reading + 1 digit
- For TDS: ± 2% of full-scale reading + 1 digit
- For temperature: ± 0.8°C/± 1.5°F
- For DO: ± 0.4 mg/L in solution
- For oxygen: 0.1% for oxygen in air
- For salt: ±0.5% of value

Measurement Resolution:
- For pH: 0.01 unit
- For ORP: 1 mV
- For conductivity: 0.1 uS @ 200 uS full-scale (f.s.), 0.001 mS @ 2 mS f.s., 0.01 mS @ 20 mS f.s., 0.1mS @ 200 mS f.s.
- For TDS: 0.1 ppm @200 ppm f.s., 1 ppm @2,000 ppm f.s., 10 ppm @ 20,000 ppm f.s., 100 ppm @ 100,000 ppm f.s.
- For temperature: 0.1°F/0.1°C
- For DO: 0.1 mg/L in solution
- For oxygen: 0.1% in air
- For salt: 0.01% of reading

Temperature Compensation:
- Automatic between 32° and 150°F (0° and 65°C) when using optional ATC temperature probe
- Manually settable between 32° and 212°F (0° and 100°C) without ATC probe

Storable/Recallable Readings: Maximum, minimum

Data Logging Sampling Time: 1 second to 9 hours

SD Card Capacity: 1 GB to 16 GB

Settable Parameters: Date, time, auto power off, beep sound, sampling time, decimal point or comma decimal division, temperature unit, compensation temperature. Also salt and altitude compensation (DO mode only)

Operating Temperature: 32° to 122°F (0° to 50°C)

Operating Relative Humidity: 0 to 85%

Power Supply: Six Alkaline "AA" batteries or optional 9-VDC AC adapter

Power Consumption:
- 14 mADC (normal operation, with backlight off and SD card not saving data)
- 37 mADC with backlight on and card saving data
- 49 mADC with backlight on and card saving data

Dimensions of Meter:
6.97 x 2.68 x 1.77 in. (177 x 68 x 45mm)

Weight of Meter: 1.08 lb. (489g)

![GENERAL®]

General Tools & Instruments
80 White Street, New York, NY 10013-3567
TEL: 212. 431. 6100   TOLL FREE: 800. 697. 8665
sales@generaltools.com   www.generaltools.com

GENERAL®

Anemometer-Thermometer

No. DAF4207SD

Pages 3-4

Hot Wire Anemometer-Thermometer

No. HWA4214SD

Pages 5-6

Environment Meter

No. DLAF930SD

Pages 7-8

Class 2 Sound Meter

No. DSM402SD

Pages 9-10

Class 1 Sound Meter

No. DSM403SD

Pages 11-12

UVA, UVC Light Meter

No. UV254SD

Pages 13-14

Light Meter

No. DLM112SD

Pages 15-16

4-Channel Thermometer

No. DT4947SD

Pages 17-18

12-Channel Temperature Recorder

No. DT4208SD

Pages 19-20

Pressure Meter

No. PM930SD

Pages 21-22

Humidity-Temperature Meter

No. DTH3007SD

Pages 23-24

Vibration Meter

No. VM8205SD

Pages 25-26

pH, ORP Meter

No. DPH230SD

Pages 27-28

Conductivity, TDS Meter

No. DCT430SD

Pages 29-30

Dissolved Oxygen Meter

No. DOM551SD

Pages 31-32

pH, ORP, DO, CD, TDS, Salt Meter

No. WK2017SD

Pages 33-34

GENERAL®

Specialty Tools & Instruments